



119 VNC

B&K Motch Single Spindle Vertical Chucker

STANDARD MACHINE SPECIFICATIONS

The Bourn & Koch Motch 119VNC is a 25" swing diameter vertical chucker, with a GE Fanuc 21iT CNC control for the chucking and vertical machining of a wide range of cylindrical components in single or multiple piece production runs.

Technical Data - Capacities & Limits	
Swing diameter	25"
Spindle Nose	A2-11
Spindle Speed Range (RPM)	280-2800
X axis slide travel (work area)	12.5"
Y axis slide travel (load area)	
Z axis slide travel	17"
Feed rate X & Z (ipm)	0-125"
No. of turret stations	6
HP	50
Height (Approximate)	
Length (Approximate)	
Width (Approximate)	
Weight (Approximate Net)	12100 lbs

Technical details subject to change without notice.

Actual machine W-H-L and Weight depend on ordered configuration. Technical data is subject to change without notice and may vary according to the workpiece geometry and options supplied. Workholding equipment supplied.



SINGLE SPINDLE VERTICAL CHUCKER



SINGLE SPINDLE VERTICAL CHUCKER

119 VNC

B&K Motch Single Spindle Vertical Chucker

Standard Equipment	
Description	
Base machine with GE 21iT CNC Control, swiveling pendant	
6 station hex turret for up to 12 tools	
Precision spindle, American Std flange nose	
Coolant distribution for turret and chip flush	
Spindle load meter	
6" hydraulic chuck actuator with drawbar	
ID/OD chuck clamping, presettable pressure	
Automatic powered door, dual push button control	
Totally enclosed chip and splash guards	
Work light	
Sealed electric cabinet with safety interlock and fans	
3 phase, 60 Hz, 460 volts	
Willy Vogel centralized lube system with safety interlocks	
Absolute encodes to retain position during power failure	
Leveling screws	
Paint: Sherwin Williams Swiss Dotted Off-White	
Documentation	
Manufactured in USA	
Standard Equipment Total (\$):	

Optional Equipment	
Description	Price (\$)
Power operated elevating chip conveyor, rear 42" discharge	
Magnetic chip conveyor	
Rosedale bag for fine filtration	
Low level coolant switch	
Oil skimmer	
"X" axis linear scale in lieu of encoder	
Foot pedal for chuck open/close	
75 HP AC spindle motor (900 rpm)	
Spindle orient package	
150 - 1500 RPM Main Spindle Speed Range	
300 - 3000 RPM Main Spindle Speed Range	
30 HP High Torque spindle drive motor	
Air Conditioner for Electrical Enclosure in lieu of standard Fan	
Contact Making Spindle Load Meter, pre-settable via "M" Code	
Spiral Bevel Gear Spindle Drive	
Special Guard for Robotic Load, including robotic interface	
Stack light	
6" diameter manifold for customer supplied mist collector	
Tool probe, column mounted	
Turret mounted part probe	
Set of leveling plates and anchor bolts	
Warranty extension to second year	
Workholding options	
GE Fanuc 21iT CNC control options	
Turret tooling	
Transformer for 3 phase, 50 Hz, 220/380/415/500 volts	
Training	
Optional Equipment Total (\$):	

Total Cost:	
Standard Equipment Total (\$):	
Optional Equipment Total (\$):	
TOTAL (\$):	

Submit a QUICK QUOTE Request



Star SU LLC
 5200 Prairie Stone Parkway, Suite 100
 Hoffman Estates, IL 60192
 USA
 Tel.: 847 649 1450
 Fax: 847 649 0112
 sales@star-su.com



BOURN & KOCH INC.
 2500 Kishwaukee Street
 Rockford, IL 61104
 USA
 Tel.: 815-965-4013
 Fax 815-965-0019
 sales@bourn-koch.com